

Advantages of Ventiflex

Ventiflex flexible ducts in grades FR and FRAS may easily be serviced by use of Ventiflex Repair Kits. Frequent inspection and subsequent repair of holes will avoid leakage and maintain the required air flow to the working area. The repair may be done in the tunnel whilst

the fan is running as well as after dismantling and preparation for storage, waiting for new installation.

The repair can be made using either:

- Hot air welding gun
- Glue

Ventiflex Repair Kit

Description

The kit comes in a wooden case including

| | |
|------------------------|------------------|
| Filament spool | 2 off |
| Chromium needle | 6 off |
| Adhesive brushes | 2 off |
| Bandage, 1.20 x 0.30 m | 6 off |
| Ventiflex FR or FRAS | 3 m ² |



To complete the Kit then order either Hand welding set or Glue set

How to order

89017000 Ventiflex Repair Kit FR or FRAS

Hand Welding Set

Repairs done by using the hot air welding gun welds the fabrics together at a temperature of approximately 400 °C and makes a strong uniform joint. The use of the hand roller enables the operator to make an air tight joint without any air bubbles.



Technical specification

Triac S-1400W / 230V-50/60Hz

How to order

89017200 Hand welder
89017300 Pressure roller

or (see next page)

Glue Set

Application

Repair by glue and cleaning liquid is recommended for use in tunnels without electrical supply or where explosive gasses are present. The process is easy to handle and can be done by anyone without training.



Safety specifications

| | |
|--------------------------|---------------------------|
| Ventlim glue | Classifications Xi, Xn, F |
| Ventanon cleaning liquid | Classifications Xi, F |

How to order

89015000 Ventlim glue 3 litres
89016000 Ventanon cleaning liquid 3 litres

Exclusive African Business Partner

HPC Products
Supply Specialists to Mining and Industry

Tel: +44 (0) 1202 587750
Fax: +44 (0) 1202 298383
Email: david@hpcproducts.com
Web: www.hpcproducts.com

Protan AS
P. O. Box 420 Brakerøya, N- 3002 Drammen, Norway
Tel. +47 32 22 16 00 Fax +47 32 22 17 00
www.protan.com